

ATS1110A-N

Advisor Advanced keypad 2x16 characters LCD

Remote arming stations

The ATS1110A is part of the Remote Arming Station family for the Advisor Advanced security system. The RAS family consists of a range of keypads and card readers which can be used in different environments, in and out-door. The ATS1110A can be used for configuration and management of the system, as well as for opening doors and arming/disarming areas. In an easy way, the ATS1110A gives a status overview from your security system with both visual and audio indicators.

Product overview

The ATS1110A is a modern ergonomic design and has a clearly readable text on a 2 x 16 characters LCD for displaying system programming, alarm and access control functions. The viewing angle of the display is adjustable via the keypad as well as the volume level of the built-in buzzer. Four arrow keys will navigate the user easily through the programming and operational features and 6 additional functions key will complete this user-friendly interface.

Indications

Four status LED's will continuously update the user on mains condition, faults, access control and alarms.

Green (Power), Yellow (Fault), Blue (Access) and Red (Alarm) are controlled by the control panel.

The Arming Station can display the status of 16 areas using 16 LED's on the front, while the LCD shows details of alarms or a pre-programmed text.

The area may be identified by viewing the 16 area LEDs visible when the RAS cover is open or removed and the indicates area is armed (on), area in fault (slow flash) and area alarm (fast flash)

Mounting

The RAS cover is hinged at the bottom. To open, grasp the cover at the sides or the top and pull gently - the cover will swing down on its pins. The cover may be fully removed by gently prising one of the pins away from the body of the RAS and pulling. The metal mounting plate at the rear is held by a locking screw.



Details

- 2 x 16 characters LCD
- User adjustable buzzer
- User adjustable LCD contrast
- 16 Area indication
- Door release indication

ATS1110A-N

Advisor Advanced keypad 2x16 characters LCD

Technical specifications

General

User interface	2 x 16 Char LCD, Touch Buttons
Product line	Advisor Advanced
Status LEDs	16

System

Function keys	4
Addressing type	DIP Switches
Supported cable type	WCAT 52/54 or equivalent

Communication

Communication type	Wired
--------------------	-------

Inputs/Outputs

Inputs	1
Input type	Request to Exit
Outputs	1
Output type	Open collector, 50 mA Max

Electrical

Operating voltage	9 to 14 VDC
Current consumption	26 mA typical 95 mA max

Physical

Physical dimensions	92 x 165 x 25,4 mm
Net weight	296 gr
Colour	White
Form factor	Vertical
Cover	Flip Cover
Mounting type	Surface mount

Environmental

Operating temperature	0 to +50°C
Relative humidity	95% noncondensing
Environment	Indoor
IP rating	IP30

Standards & regulation

EN50131 grade	Grade 3
Compliance	CE, RoHS
Certification	VdS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 November 2021 - 22:27