

Electric strike 115RR- - - - - D15

Without strike plate, 6-12 V AC/DC



Product description

Model with monitoring contact as potential-free changeover contact. This is actuated by the latch bolt via a lever.

Technical data

Dimensions	Depth: 33 mm , Height: 90.5 mm , Width: 23 mm
Mounting	asymmetrical
Configuration	Frame component
With fixing	No
With mechanical unlocking	No
With feedback signal	Yes
Waterproof	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
How they work	Fail-locked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	Yes
Adjustable electric strike	No
Unlocking type	Standard version
Mechanical unlocking	No
Suitable for smoke protection door	No
With strike plate	No
Max. latch preload DC	30 N
Min. preload DC	10 N
Latch adjustment range	3 mm
Contact load capacity monitoring contact	1 A
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	Yes
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Latch version	Standard latch
Voltage	6-12 V
Version	other
Break-in resistance	3000 N
Operating temperature range	-15-40 °C
Installation position	vertical
Opening direction according to DIN	right
Mounting method	Installation
Type of current	AC/DC
Adjustable strike plate	No
Latch bolt guide integrated	No
For latch bolt slide	No
Permanent operation (100% power-on time)	No
Suitable for fire door	No
Max. latch preload AC	120 N
Min. preload AC	80 N
max. current consumption AC	1100 mA
Max. current consumption DC	1560 mA
Nominal resistance 12 V	7.7 Ohm
Article number	115RR-----D15
EAN	4042203018426