

Electric strike 125E- - - - - D15

Without faceplate, 6-12 V AC/DC, DIN right

Product description

Model with mechanical permanent unlocking system in keeper.



Technical data

| | |
|--|---|
| Dimensions | Depth: 33 mm , Height: 88 mm , Width: 23 mm |
| Mounting | asymmetrical |
| Installation position | vertical |
| Configuration | Frame component |
| With fixing | Yes |
| With mechanical unlocking | Yes |
| With feedback signal | No |
| Waterproof | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| How they work | Fail-locked |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |
| Pulse contact | Yes |
| Adjustable keeper | Yes |
| Adjustable electric strike | No |
| Unlocking type | Standard version |
| Mechanical unlocking | Yes |
| Suitable for smoke protection door | No |
| With strike plate | No |
| Max. latch preload DC | 30 N |
| Min. preload DC | 10 N |
| Latch adjustment range | 3 mm |
| Load cycles for in-plant test | 250000 |
| Changeable connection | No |
| Clampable/ plug-in connection | Yes |
| Protective diode | No |
| Noise reduction | No |
| Drill hole offset by 1 mm | No |
| Unlocking time | 0.8 s |
| Latch version | Standard latch |
| Voltage | 6-12 V |
| Version | other |
| Break-in resistance | 3000 N |
| Operating temperature range | -15-40 °C |
| Opening direction according to DIN | right |
| Mounting method | Installation |
| Type of current | AC/DC |
| Adjustable strike plate | No |
| Latch bolt guide integrated | No |
| For latch bolt slide | No |
| Permanent operation (100% power-on time) | No |
| Suitable for fire door | No |
| Max. latch preload AC | 120 N |
| Min. preload AC | 80 N |
| max. current consumption AC | 1100 mA |
| Max. current consumption DC | 1560 mA |
| Nominal resistance 12 V | 7.7 Ohm |

| | |
|----------------|---------------|
| Article number | 125E-----D15 |
| EAN | 4042203146396 |