

Electric strike

Without strike plate, 12 V DC eE, DIN right

Product description

Model with mechanical permanent unlocking system in keeper.



Technical data

Dimensions	Depth: 33 mm , Height: 88 mm , Width: 23 mm
Mounting	asymmetrical
Installation position	vertical
Configuration	Frame component
With fixing	Yes
With mechanical unlocking	Yes
With feedback signal	No
Waterproof	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
How they work	Fail-locked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	Yes
Adjustable electric strike	No
Unlocking type	Standard version
Mechanical unlocking	Yes
Suitable for smoke protection door	No
With strike plate	No
Max. latch preload DC	30 N
Min. preload DC	10 N
Latch adjustment range	3 mm
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	Yes
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Latch version	Standard latch
Voltage	12 V
Version	other
Break-in resistance	3000 N
Operating temperature range	-15-40 °C
Opening direction according to DIN	right
Mounting method	Installation
Type of current	DC
Permanent operation (100% power-on time)	Yes
Suitable for fire door	No
Max. latch preload AC	80 N
Min. preload AC	50 N
max. current consumption AC	130 mA
Max. current consumption DC	200 mA
Nominal resistance 12 V	60 Ohm
Nominal operating voltage tolerance	+ - 1 V

Article number	125E-----E35
EAN	4042203369849