

Electric strike

Without strike plate, 12 V DC, DIN right

Product description

Model with monitoring contact as potential-free changeover contact. This is actuated by the latch bolt via a lever.

Technical data

Dimensions	Depth: 33 mm , Height: 90.5 mm , Width: 23 mm
Mounting	asymmetrical
Installation position	vertical
Configuration	Frame component
With fixing	No
With mechanical unlocking	No
With feedback signal	Yes
Waterproof	No
Mounting method	Installation
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Type of current	DC
How they work	Fail-unlocked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	Yes
Adjustable electric strike	No
Unlocking type	Standard version
Permanent operation (100% power-on time)	Yes
Mechanical unlocking	No
Suitable for smoke protection door	No
With strike plate	No
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	Yes
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Latch version	Standard latch
Voltage	12 V
Version	other
Break-in resistance	3000 N
Operating temperature range	-15-40 °C
Suitable for fire door	No
Opening direction according to DIN	right
Max. current consumption DC	195 mA
Contact load capacity monitoring contact	1 A
Nominal resistance 12 V	61 Ohm
Nominal operating voltage tolerance	+ - 1 V
Article number	135RR-----E95
EAN	4042203205772

