

Electric strike 27- - - - - F41

Without striking plate, 24V DC 100%ED

Product description

Model with basic equipment.

Overview of Advantages

- Suitable for all common striking plates
- Due to 180° fitting, can be used DIN right and left
- Symmetrical design

Technical data

Dimensions	Height: 75 mm , Width: 20.5 mm , Depth: 28 mm
Version	Standard electric strikes
Latch version	Standard latch
Mounting	symmetrical
Installation position	universal
Configuration	Frame component
With fixing	Yes
With mechanical unlocking	No
With feedback signal	No
Opening direction according to DIN	left/right
Waterproof	No
Mounting method	Installation
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
How they work	Fail-locked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	Yes
Adjustable electric strike	No
Unlocking type	Standard version
Mechanical unlocking	No
Suitable for smoke protection door	No
Break-in resistance	3500 N
Min. preload DC	10 N
Latch adjustment range	3 mm
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	No
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Operating temperature range	-15-40 °C
Certified in compliance with	EN 14846
Suitable for fire door	No
Voltage	24 V
Type of current	DC
Permanent operation (100% power-on time)	Yes
Max. latch preload DC	20 N
Max. current consumption DC	120 mA
Continuous duty	22-26 V
Nominal resistance 12 V	190 Ohm
Nominal operating voltage tolerance	+ - 2 V

Article number	27-----F41
EAN	4042203095779

