

# Electric strike 27E-----E41

Without striking plate, 12V DC 100%ED

## Product description

Model with mechanical unlocking.

## Overview of Advantages

- Suitable for all common striking plates
- Due to 180° fitting, can be used DIN right and left
- Symmetrical design

## Technical data

Dimensions	Height: 75 mm , Width: 20.5 mm , Depth: 28 mm
Version	Standard electric strikes
Latch version	Standard latch
Mounting	symmetrical
Installation position	universal
Configuration	Frame component
With fixing	Yes
With mechanical unlocking	Yes
With feedback signal	No
Opening direction according to DIN	left/right
Waterproof	No
Mounting method	Installation
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
How they work	Fail-locked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	Yes
Adjustable electric strike	No
Unlocking type	Standard version
Mechanical unlocking	Yes
Suitable for smoke protection door	No
Break-in resistance	3500 N
Min. preload DC	10 N
Latch adjustment range	3 mm
Load cycles for in-plant test	250000
Changeable connection	No
Clampable/ plug-in connection	No
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Operating temperature range	-15-40 °C
Certified in compliance with	EN 14846
Suitable for fire door	No
Voltage	12 V
Type of current	DC
Permanent operation (100% power-on time)	Yes
Max. latch preload DC	30 N
Max. current consumption DC	270 mA
Continuous duty	11-13 V
Nominal resistance 12 V	44 Ohm
Nominal operating voltage tolerance	+ - 1 V

Article number	27E-----E41
EAN	4042203096653

