

Product description

Electric motor bolt for doors, gates and roller shutters with high security demands. For outdoor and indoor use.

Overview of Advantages

- Holding force: 39,000 N
- designed for outdoor use, protection class IP67
- integrated heating, can be switched on via dip switch
- fail-locked/fail-unlocked configurable via dip switch
- push-button/switch function configurable via dip switch (Toggle mode)
- multi-voltage 12V DC to 24V DC (heating only 24V DC)
- various monitoring contacts
- anti-tamper contact
- mounting position vertical and horizontal

Scope of delivery

- drop bolt 843G with 3 metre connection cable, with housing base seal, incl. counterpart

Note

- Please note the installation instructions
- For vertical mounting position, the locking direction is recommended to close downwards.

Technical data

Dimensions	Height: 150 mm , Width: 80 mm , Depth: 80 mm
Version	other
Latch version	other
Mounting	other
Configuration	complete
Voltage	12-24 V
With feedback signal	Yes
Waterproof	Yes
Mounting method	applied
Type of current	DC
Forend shape	square
With strike plate	Yes
Strike plate shape	Angled
Strike plate material	other
Base colour of the strike plate	black
Strike plate length	80 mm
Strike plate width	80 mm
Strike plate thickness	60 mm
Max. latch preload DC	39000 N
Max. current consumption DC	1000 mA
Nominal operating voltage tolerance	+ - 15%

Article number	843G-1-----Q41
EAN	4042203778559

