



Fuse-link, LV, 10 A, AC 500 V, D1, gL/gG, IEC, time-delay

Catalog No. 10D16
EL-Nummer (Norway) 0001601250

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	10
Rated voltage			AC 500 V
Construction size			D1
Utilization category			gL/gG
usable for size/applications			E16 for domestic and general industrial applications
Release characteristic	class		time-delay
Standard/Approval			IEC
Standards/Regulations			IEC 60269-3 VDE 0636

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / D-system fuse link (EC000099)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Diazed fuse link (ec @ss10.0.1-27-14-20-04 [AFZ799015])			
Construction size			D1
Rated current		A	10
Rated voltage		V	500
Colour code			Red
Utilization category			gL/gG (cable protection/equipment protection)
Release characteristic			Time-lag

Additional product information (links)

Product datasheet (PDF)	http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-4124-danddofuselinks.pdf
-------------------------	---