



Fuse-link, LV, 20 A, AC 500 V, NH000, gL/gG, IEC, dual indicator, live gripping lugs

Catalog No. 20NHG000B

EL-Nummer (Norway) 0001664005

Delivery program

| | | | |
|-----------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 20 |
| Rated voltage | | | AC 500 V |
| Construction size | | | NH000 |
| Utilization category | | | gL/gG |
| Status indicator | | | dual (combination) indicator system |
| Description | | | live gripping lugs |
| Breaking Capacity | | kA | 120 |
| Standard/Approval | | | IEC |
| Shape | | | square body with knife blade contacts |
| Standards/Regulations | | | IEC 60269-2 fuse system A DIN 43620 VDE 0636-2 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | NH000 |
| Rated current | | A | 20 |
| Rated voltage | | V | 500 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 120 |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator | | | Combination fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbusssmann.com/pdf/dd9b7025-0e58-46b4-b717-66ce5e12c2b8.pdf |
|-------------------------|---|