



Fuse-link, LV, 400 A, AC 500 V, NH2, gL/gG, IEC, dual indicator, live gripping lugs

**Catalog No.** 400NHG2B

**EL-Nummer (Norway)** 0001664074

### Delivery program

|                       |   |    |  |
|-----------------------|---|----|--|
| Product range         |   |    | Fuse   |
| Basic function        |   |    | Fuse-link  |
| Field of application  |   |    | low voltage  |
| Rated current         | I | A  | 400  |
| Rated voltage         |   |    | AC 500 V   |
| Construction size     |   |    | NH2  |
| Utilization category  |   |    | gL/gG  |
| Status indicator      |   |    | dual (combination) indicator system                  |
| Description           |   |    | live gripping lugs                                   |
| Breaking Capacity     |   | kA | 120  |
| Standard/Approval     |   |    | IEC  |
| Shape                 |   |    | square body with knife blade contacts                |
| Standards/Regulations |   |    | IEC 60269-2 fuse system A<br>DIN 43620<br>VDE 0636-2 |

### Technical data ETIM 7.0

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |   |
| Construction size   |  |    | NH2   |
| Rated current   |  | A  | 400   |
| Rated voltage   |  | V  | 500   |
| Voltage type  |  |    | AC  |
| Rated switching capacity  |  | kA | 120   |
| Utilization category  |  |    | gL/gG (cable protection/equipment protection) |
| Type of fuse status indicator   |  |    | Combination fuse status indicator             |
| Insulated metal gripping lugs (IMGL)  |  |    | No  |

### Additional product information (links)

|                         |   |
|-------------------------|---|
| Product datasheet (pdf) | <a href="http://www1.cooperbusssmann.com/pdf/dd9b7025-0e58-46b4-b717-66ce5e12c2b8.pdf">http://www1.cooperbusssmann.com/pdf/dd9b7025-0e58-46b4-b717-66ce5e12c2b8.pdf</a> |
|-------------------------|---|