



Fuse-link, LV, 40 A, AC 690 V, 22 x 58 mm, gL/gG, IEC

Catalog No. C22G40

EL-Nummer (Norway) 0001600224

Delivery program

| | | | |
|------------------------------|---|---|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | low voltage |
| Rated current | I | A | 40 |
| Rated voltage | | | AC 690 V |
| Size | | | 22 x 58 mm |
| Utilization category | | | gL/gG |
| usable for size/applications | | | for industrial applications for general purpose use |
| Standard/Approval | | | IEC |
| Shape | | | cylindrical |
| Standards/Regulations | | | IEC 60269-2 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) | | | |
| Size | | | 22x58 mm |
| Rated voltage | | V | 690 - 690 |
| Rated voltage | | | Other |
| Voltage type | | | AC |
| Utilization category | | | gL/gG (cable protection/equipment protection) |
| Rated operating frequency | | Hz | 45 - 62 |
| Nominal current | | A | 40 |
| With striker | | | No |
| Release characteristic | | | Other |
| Breaking capacity | | kA | 80 |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (PDF) | http://www.cooperindustries.com/content/dam/public/bussmann/iec-electrical/resources/data-sheets/bus-iec-ds-720115-cylindricalfuselinks.pdf |
|-------------------------|---|