

1-core indoor cable termination
with screw cable lugs for 1-core polymeric cables

Hybrid cable terminations CHESK-I are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (copper wire or tape). With screw cable lugs for main conductor and copper wire screen.



Product description

Article name	CHESK-I 36kV 16-95
Article number	309527
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)

Characteristics

- Flexible silicone stress control elements ensure reliable stress control under all operating conditions
- Combination of slip-on and heat shrinkable components
- Wide cross-section range
- Quick, safe and easy assembly
- Ready for immediate operation

Applications

Indoor

Technical data



Article name	CHESK-I 36kV 16-95
Article number	309527
Voltage levels	U0/U (Um) 18/30 (36) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	500 mm
Diameter over core insulation after removal of the outer conductive layer min	19.9 mm
Number of sheds per phase	2 Pieces
Diameter shed	85 mm
Nominal cross section 36 kV min	16 mm ²
Nominal cross section 36 kV max	95 mm ²

Logistics data

Article name	CHESK-I 36kV 16-95
Article number	309527
Delivery scope	Heat shrinkable tube (tracking resistant)
	Silicone field control elemens
	Silicone sheds
	Screw cable lugs
	1 Set for 3 phases
	Sealing tape
	Assembly material
	Installation instruction
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311160948

Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	42
Unit of measure	Piece	Piece
Lenght (mm)	730	1200
Width (mm)	165	800
Height (mm)	157	1130
Net weight (kg)	1.998	83.916
Gross weight (kg)	1.998	102.116