

TUBOLED GLASS GLL



- * Base: G13.
- * LED tubes completely enveloped in glass filled with phosphor powder.
- * Wide lighting distribution curve.
- * Color rendering > 80.
- * Operating voltage 220-240V.
- * Working position: universal.
- * Replacing fluo T8 tubes: high energy saving.
- * Immediate switch on, no flickering or buzzes.
- * Great flow maintenance.
- * Packed like fluorescent tubes. Min. order quantity is 10pcs.
- * USAGE INFORMATION
- * Do not use with dimmers.
- * In case fluorescent tubes must be replaced, follow the simple assembly instructions on the mounting instruction sheet.
- * Do not use in installations in series.

Item Characteristics

Code	L36840GLL
Lamp Voltage	220-240 V
Nominal Power	17 W
Base	G13
Lamp Current	0,08 A
Nominal Flux	1900 LUMEN
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	300°
Diameter	28 mm
Lenght	1213 mm

Performance

Irc/Ra	>80
Lifetime	40000 h
Energy Class	A+
kWh/1000h	17
Equivalence with incandescent lamp	121 W

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,9
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C

Shipping info

Item barcode	8011905845674
Pack	10 pz