

# Eaton 167113

Catalog Number: 167113

Eaton Moeller series xEffect - FRCmM-NA RCCB. Residual current circuit breaker (RCCB), 25A, 2p, 30mA, type A, UL



### General specifications

#### Product Name

Eaton Moeller series xEffect - FRCmM-NA RCCB

#### Catalog Number

167113

#### Model Code

FRCMM-25/2/003-A-NA

#### EAN

4015081636150

#### Product Length/Depth

80 mm

#### Product Height

71 mm

#### Product Width

35 mm

#### Product Weight

0.22 kg

#### Compliances

RoHS conform

#### Certifications

UL 1053  
IEC/EN 61008  
EN45545-2  
IEC 61373

#### Catalog Notes

Protects against special forms of residual pulsating DC which have not been smoothed.

## Product specifications

### Used with

Type A

Residual current circuit breakers

FRCmM-NA

### Type

FRCmM-NA

Residual current circuit  
breakers

Type A

### Special features

Current test marks as per  
inscription

Maximum operating  
temperature is 55 °C:

Starting at 40 °C, the max.

permissible continuous  
current decreases by 3% for  
every 1 °C

The maximum operating  
current of back-up fuse must  
not exceed the residual  
current circuit breaker's  
rated operational current

### Application

Switchgear for export to North America (UL-listed)

### Amperage Rating

25 A

### Features

Additional equipment possible

Residual current circuit breaker

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the

## Resources

### Application notes

[eaton-rcc-application-guide-br019003en-en-us.pdf](#)

### Catalogs

[eaton-xeffect-frcmm-na-rccb-catalog-ca003019en-en-us.pdf](#)

[eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf](#)

### Declarations of conformity

[03\\_FRCm.-NA\\_181019](#)

[DA-DC-03\\_FRCm](#)

### Drawings

[eaton-circuit-breaker-xeffect-frcmm-na-rccb-dimensions.eps](#)

[Mas\\_frcmm](#)

### eCAD model

[ETN.FRCMM-25\\_2\\_003-A-NA](#)

### Installation instructions

[MA180503312](#)

### mCAD model

[eaton-f9\\_ul1053\\_2p-3-d-model.stp](#)

[eaton-cadenas-path-03-geo-f9\\_ul1053\\_2p.3db](#)

[eaton-cadenas-side\\_view-f9\\_ul1053\\_2p\\_side.pra](#)

[eaton-cadenas-front\\_view-f9\\_ul1053\\_2p\\_front.pra](#)

[eaton-f9\\_ul1053\\_2p-drawing.dwg](#)

### Specifications and datasheets

[Eaton Specification Sheet - 167113](#)

### Wiring diagrams

[PFIM\\_2p](#)

[eaton-circuit-breaker-xeffect-frcmm-na-rccb-wiring-diagram.eps](#)

[eaton-xeffect-frcmm-rccb-wiring-diagram.jpg](#)

[FRCmM-2p](#)

switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Fitted with:

Interlocking device

#### Frame

45 mm

#### Frequency rating

50 Hz / 60 Hz

#### Pollution degree

2

#### Mounting Method

Quick attachment with 2 latch positions for DIN-rail IEC/EN

60715

DIN rail

#### Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

#### Equipment heat dissipation, current-dependent

2 W

#### Rated impulse withstand voltage (Uimp)

4 kV

#### Rated short-time withstand current (Icw)

10 kA

#### Admissible back-up fuse overload - max

25 A gG/gL

#### Ambient humidity range

5 - 95 %

#### Built-in width (number of units)

35 mm (2 SU)

#### Short-circuit rating

Max. admissible back-up fuse: 63 A gG/gL, 70 A class J fuse  
(UL)

#### Status indication

White / blue

#### Terminal protection

Finger and hand touch safe, DGUV VS3, EN 50274

#### Terminals (top and bottom)

Lift terminals

#### Test circuit range

184 V AC - 440 V AC, 196 V AC - 305 V AC (UL)

#### Ambient operating temperature - max

40 °C

#### Ambient operating temperature - min

-25 °C

#### Built-in depth

70.5 mm

#### Connectable conductor cross section (multi-wired) - max

16 mm<sup>2</sup>

#### Connectable conductor cross section (multi-wired) - min

1.5 mm<sup>2</sup>

#### Connectable conductor cross section (solid-core) - max

35 mm<sup>2</sup>

#### Connectable conductor cross section (solid-core) - min

1.5 mm<sup>2</sup>

#### Fault current rating

30 mA

#### Heat dissipation capacity

0 W

#### Heat dissipation per pole, current-dependent

1 W

#### Overvoltage tested - max

530 V

#### Permitted storage and transport temperature - max

60 °C

#### Permitted storage and transport temperature - min

-35 °C

#### Contact position indicator color

Red / green

#### Mounting position

As required

#### Lifespan, mechanical

10000 operations

Degree of protection

IP20, IP40 with suitable enclosure

IP20

Impulse withstand current

250 A (8/20  $\mu$ s) surge-proof

Partly surge-proof 250 A

Number of poles

Two-pole

Leakage current type

A

Lifespan, electrical

4000 operations

Pick-up current

22 mA

Sensitivity type

Pulse-current sensitive

Terminal capacity (cable)

M5 (with cross-recessed screw as defined in EN ISO 4757-Z2,  
PZ2)

Rated fault current - max

0.03 A

Rated fault current - min

0.03 A

Rated insulation voltage (Ui)

440 V

Rated operational current for specified heat dissipation (In)

25 A

Rated operational voltage (Ue) - max

277 V

Rated residual making and breaking capacity

500 A

Static heat dissipation, non-current-dependent

0 W

Surge current capacity

0.25 kA

Width in number of modular spacings

2

Voltage rating (IEC/EN 60947-2)

240 V AC / 415 V AC

Voltage rating (UL)

480Y/277 V, 60 Hz

Voltage type

AC

Terminal capacity (solid wire)

1.5 mm<sup>2</sup> - 35 mm<sup>2</sup>

Tripping time

Non-delayed

Rated short-circuit strength

5 kA (UL, as per CSA)

10 kA with back-up fuse

Terminal capacity (stranded cable)

16 mm<sup>2</sup> (2x)

RAL-number

7035



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)