

ECGFE10

FLEXIBLE SPIRAL CONDUIT 23114 Ø10 mm - 30 m - GREY



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Conduits and fittings > Spiral conduits > Flexible spiral conduits
> Series gfe - class 23114 - 750n > Spiral flexible conduits > Grey

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
UV resistant	Yes	Working temperature	5-60 °C	Nominal diameter	10 mm
Inner diameter	10 mm	Outer diameter	14.7 mm	Compressive strength	320 N
Bending radius, static	100 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Yes
Approved according to UR	Yes	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Yes	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download



Certification

Certificato UL
GUAINA E173313-
2021.pdf

Barcode



8050880888450

Cardboard

30 MT

0.34x0.34x0.135 [m]

2.199 [kg]



8057711593774

Pallet

6840 MT

501.372 [kg]