

ECGFE16

FLEXIBLE SPIRAL CONDUIT 23114 Ø16 mm - 30 m - GREY



IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Conduits and fittings > Spiral conduits > Flexible spiral conduits
> Series gfe - class 23114 - 750n > Spiral flexible conduits > Grey

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
UV resistant	Yes	Working temperature	5-60 °C	Nominal diameter	16 mm
Inner diameter	16 mm	Outer diameter	20.7 mm	Compressive strength	320 N
Bending radius, static	160 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Yes
Approved according to UR	Yes	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Yes	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Documentation available for download



Certification

Certificato UL
GUAINA E173313-
2021.pdf



Certification

Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8054320282655

Cardboard

30 MT

0.425x0.425x0.11 [m]

3 [kg]



8059307210805

Pallet

5400 MT

540 [kg]