

# ENSTO

KE10.506

## Leágazó csatlakozó

Típus KE10.506  
 GTIN 6418677400094  
 Név Leágazó csatlakozó  
 Al 6x10-50 mm<sup>2</sup> / Cu 2.5-35 mm<sup>2</sup>  
 Leírás KE10.506 csatlakozó alkalmazható AL és Cu vezeték összekötésére. Meghúzási nyomaték 10 Nm. A csatlakozó szerelhető lámpaoszlopba vagy külön dobozba.




## Műszaki specifikáció

### Méreték

Súly: 0.07 kg  
 Hossz: 91 mm  
 Magasság: 38 mm  
 Vezeték keresztmetszet Al: 10 ... 50 mm<sup>2</sup>  
 Vezeték keresztmetszet Cu: 2.5 ... 35 mm<sup>2</sup>  
 Vezeték átmérő: 2 ... 10.2 mm

### Villamos paraméterek

Max. rendszer feszültség: 1 kV

### Szín

Szín: Átlátszó

### Mechanikai

Meghúzási nyomaték: 10 Nm

### Szabványok

Szabványok: IEC 61238-1

### Névleges

ETIM 7: EC000306 Low current connector

ETIM

**ETIM**

<b>Grease filling against corrosion:</b>	true
<b>Colour insulation:</b>	Transparent
<b>Interrupt free shifting:</b>	true
<b>Material insulation:</b>	PC
<b>Nominal cross section:</b>	2.5 ... 50 mm <sup>2</sup>
<b>Model:</b>	Branch
<b>Max. number of cores:</b>	1
<b>Core diameter:</b>	2 ... 10.2 mm

**Csomagolás**

---

**Csomagolás**

<b>Unit:</b>	PCS
<b>Size:</b>	50
<b>Length:</b>	220 mm
<b>Width:</b>	220 mm
<b>Height:</b>	175 mm
<b>Weight (net):</b>	3.5 kg
<b>Weight (brt):</b>	3.647 kg
<b>Volume:</b>	0.0085

**Pallet package**

<b>Size:</b>	3500
<b>Length:</b>	1200 mm
<b>Width:</b>	800 mm
<b>Height:</b>	840 mm
<b>Weight (net):</b>	245 kg
<b>Weight (brt):</b>	265 kg
<b>Volume:</b>	0.8064

