

FE240 Door Holder, Flush Mounting, 400N

General

The FE240 is a flush mount door holder, with a Bayblend housing, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic housing is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.

- The housing is predrilled in a practical, standard format for rapid mounting.

- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE240 is fully approved according to EN1155.



Details

- Low power 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE240 Door Holder, Flush Mounting, 400N

Technical specifications

- ·	
General	
Holding force N (Newton)400	
Release button	No
Spark supression diode	Yes
Reverse polarity protection	Yes
Electrical	
Power supply type	24 VDC
Power consumption	1.6 W
Duty cycle	100%
Physical	
Physical dimensions	85 x 85 x 35 mm (H x W x D)
Environmental	
IP rating	IP54 (magnet)
	IP42 (connection)
Standards & regulation	
Standards	EN1155



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.