





## LongLast<sup>™</sup> Spiral T2 -15,000 hours ot#FLE20HLX/T2/827/E27 GE 1/6T 15Y /01 **76158**

# **Product information**

LongLast<sup>™</sup> T2 Spiral Compact Fluorescent Lamp (CFL) is the smallest size long life CFL lightbulb in the market. This unique GE product offers excellent light quality over it's 15,000 hours lifetime and can be used in any indoor or outdoor applications.

#### **Application areas**





Healthcare

Hospitality





### Product data

Product Code	76158
Bulb Shape	Heliax
Bulb Diameter [mm]	10
Bulb maximum overall diameter [mm]	56
Nominal Length [mm]	118
Maximum Overall Length [mm]	544
Net weight per piece [g]	67
Gross weight per piece [g]	95
Operating position	U - Universal
Mercury Content [mg]	0.85
UV radiance	exempt
Brand	General Electric (GE)
Cap/Base	E27

### Performance data

Colour Code	827
Energy efficiency class (EEC)	А
Rated Life [h]	15000
Nominal correlated colour temperature (CCT) [K]]	2700
Nominal lumens [lm]	1220
Colour Rendering Index (CRI) [Ra]	80





#### **Electrical data**

Lamp Current [A]	167
Operating Temperature (MIN) [°C]	-15
Operating Temperature (MAX) [°C]	50
Starting ambient temperature range	-15
Startup time [sec]	1.5
Dimming Capability	No
Nominal power [W]	20
Nominal lamp voltage [V]	230

## Logistic data

10043168761588
0043168761581
6
228 EUR, 282 UK
228
282
1596
1974
128 x 187 x 138 (mm)
Phased-out





#### Survival data







#### **Downloads & Links**

Go to the catalog site (HTTP) CFL Integrated Spectrum Catalogue (PDF) LongLast<sup>™</sup> T2 Spiral Lamps Data sheet (PDF) Lighting design tools & calculators (HTTP) Disposing and Cleaning of CFL Lamps (HTTP) CFL Integrated Spectrum Catalogue (PDF) Disposing and Cleaning of CFL Lamps (HTTP) Lighting design tools & calculators (HTTP) Datasheets (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)