







GE Start Candle LED5.5/B35/827/E14/220-240V/FR

93063960

Product information

GE's new entry level range, the LED Start Decorative Candle lamps offer real cost out opportunities versus Halogen lamps. Features such as standard IEC dimensions and 15,000 hours rated life with high lumen output creates a highly competitive range.

Application areas



(A) Hospitality



Home





Product data

RoHS compliant Yes Brand GE BX	Product Code	93063960
Bulb Diameter [mm] 35 Nominal Length [mm] 107 Net weight per piece [g] 29 RoHS compliant Yes Brand GE BX	Bulb Shape	B35
Nominal Length [mm] 107 Net weight per piece [g] 29 RoHS compliant Yes Brand GE BX	Bulb Finish	white
Net weight per piece [g] 29 RoHS compliant Yes Brand GE BX	Bulb Diameter [mm]	35
RoHS compliant Yes Brand GE BX	Nominal Length [mm]	107
Brand GE BX	Net weight per piece [g]	29
	RoHS compliant	Yes
Cap/Base F14	Brand	GE BX
Cap, 2000	Cap/Base	E14

Performance data

Rated efficacy [lm/W]	85
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	10 000
Nominal correlated colour temperature (CCT) [K]]	2700
Nominal lumens [lm]	470
Colour Rendering Index (CRI) [Ra]	80

Electrical data

Nominal lamp power factor	>0.5
Operating Temperature (MIN) [°C]	-20°C
Operating Temperature (MAX) [°C]	+40°C
Startup time [sec]	<0.5
Power Factor	>0.5
Number of switching cycles	50 000
Dimming Capability	No
Nominal lamp voltage range [V]	220-240V
Nominal power [W]	5.5





GE Start Candle LED5.5/B35/827/E14/220-240V/FR

93063960

Logistic data

DUN Code	10064894571975
EAN Code	0064894571978
Pack Quantity	10
Inner pack type	Box
Outer pack type	Carton
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Product range datasheet (PDF)

LED Lighting Solutions - Catalogue (PDF)

Lighting design tools & calculators (HTTP)

Candle range Datasheets (HTTP)

GE Start Candle range images (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)