



Lightech 100/150/200W ot LED200CV24EMS GE **97745**

Product information

Lightech 100-200W

- 100W, 150W, 200W drivers, with 12V & 24V output.
- 0.99 Power Factor & 0.92 Efficiency.
- Class II, IP67 Extruded Metal housing with Side Leads.
- Max Tc 80°C (100W), 90°C (150/200W).
- White/Silver case for Signage Applications.





Product data

Product Code	97745
Class II	Yes
ENEC	Yes
SELV	Yes
Product colour	White
Storage Temperature [°C]	-25 / +70
Dimmable	No
Form factor	Extrusion SL
Height [mm]	42
Length [mm]	230
Width [mm]	66
IP	67
Weight [g]	950
IP67	Yes

Performance data

Colour (product colour)	White
Ambient temperature min. [°C]	-25 °C
Ambient temperature max. [°C]	60 °C
Case temperature [°C]	90 °C
Power factor	0.99
Efficiency [%]	92





Electrical data

Input frequency	0/50/60Hz
Output voltage range	24V
Drive Current [mA]	max 8.3A
Input voltage range	220-240V
Nominal power [W]	200
Nominal lamp voltage [V]	230

Logistic data

Product status

Available

Disclaimer

This product is intended to be used as a lamp control gear that has to be installed after the mains control switch.