



ELIA OL




ELIA OL is an elegant die-cast aluminum fixture for wall mounting, ideal for indoor and outdoor architectural lighting such as: stairs, passageways or facades, quick and easy to install, with a clean and essential line. Designed in two different finishes (black and white), with double emission diffusing polycarbonate opal screen (top and down) to create a comfortable atmosphere, color temperatures of 3,000K, 4,000 K and 5,700 K and a color rendering index greater than 80. It has been designed to withstand temperature variations from -20 ° C to + 45 ° C, water and dust penetration up to IP65 degree and shocks up to IK08 degree. Light and handy ELIA OL is easy to install thanks also to the rear bracket for fixing, the quick-fit terminal placed in the back for the electrical wiring.

GENERAL INFORMATION		OPTIC AND ILLUMINATING FEATURES	
Context	Illuminazione architetture esterna e interna	Optika	Wide opal
Luminaire	LED luminaire for accentuation	Unified Glare Rating	UGR ≤ 25
Alkalmazás	Beltéri / Kültéri	Fényáram kibocsátás (lm)	650
Unique digital code (Datamatrix)	Currently not present	Efficiency (lm/W)	81
Szín	Fekete	Szín hőmérséklet	3000 K
Fényforrás típusa	LED	Color Rendering Index	CRI 80
Rendszer teljesítmény	8 W	Standard Deviation Colour Matching	SDCM = 5
LED Lifetime	L80B50 (Tq25°) = 50.000h	Photobiological Risk Class	RG0
Súly (kg)	0.5	Szabvány	EN 60598-1; EN 60598-2-1; IEC/TR 62778; EN 62493
Garancia időtartam	5 év	ELETRICAL AND LIGHTING FEATURES	
Tárolási hőmérséklet	-20° +65°	Elektromos feszültség	100-240 V
Operating temperature	-20° +45°	Névleges frekvencia	50/60 Hz
MATERIALS		Driver	Beépített
Body	DMN	Driver failure rate	F025 (Tq=25°C) = 50.000 h
Búra típusa	Polycarbonate	Overvoltage protection	DM 0,5KV / CM 1KV
Optic	Diffusore in policarbonato biemissione	Control System	ON / OFF
Gasket	-	INSTALLATION AND MAINTENANCE	
Locking Hook	-	Mounting and installation	Falra szerelhető
External screw	Stainless steel	Tilt	-
Colour	Powder coating	Wiring	With connection terminal
STANDARDS AND APPROVALS		Rögzítés	Tramite supporto in acciaio inossidabile
Besorolás	-	Light souce replaceability	Non-replaceable
Berendezés	-	Controlgear replaceability	Non-replaceable
csökkentett felületi hőmérséklettel	-	Driver Box	Beépített
DIN 18032-3 tanúsítvány	-	Maximum surface exposed to the wind	-
IPEA	Aree Verdi B	-	-
Érintésvédelmi osztály	I	-	-
IP védettség szintje	IP65	-	-
Útés állóság	IK08	-	-
Glow Wire Test	750 °C	-	-

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



ELIA OL

TECHNICAL SYMBOLOGY



IP
IP65

IK
IK08

GWT
750 °C

STANDARDS/APPROVALS

