

## Fire-protection cavity wall box



### One-gang box HWD 68

- for EI 30 - EI 90 fire-protection walls
- also for directly opposing installation
- minimum wall thickness 100 mm
- can be combined with each other and with the one-gang junction box

<b>Order number:</b>	<b>9463-02</b>
EAN:	4013456546202
Depth	49 mm
Cut hole Ø	68 mm
Screw spacing	60 mm
Support connectors for each package	5
DIBt approval	Z-19.21-2321
ETA approval	ETA-18/0418
Cable entries of up to Ø 11.5 mm	6
for sound insulation walls up to	69 dB
For panel thicknesses up to	40 mm
Halogen-free	Yes
Packaging inner/dispatch	10/100

Fire-protection boxes HWD 68 are given the same period of fire resistance in fire-protection walls EI30 - EI90 in spite of fitted electrical installations and ensure secure, smokeproof room separation. In the event of a fire, an integrated fire retardant quickly and reliably closes the installation opening and prevents flames and flue gases from escaping. This ensures that lives are saved and material goods are efficiently protected.

- For fire-protection walls EI30-EI90
- Maintains the wall's sound insulation protection
- Retrofitting is possible
- For Ø 68 mm component openings
- For directly opposing installation
- Break-out cable entry
- With fire-protection cover, can be used as a junction box

