

Product code: 201231 EAN: 5905378201231

LED line PRIME controller VARIANTE LED RF WIFI TUYA RGB CCT



Product description

Manufacturer issues a 5-year warranty for this product. This product offers the benefit of controlling the light with the use of smartphone from any place in the world via IoT TUYA system. The user can control not only the brightness in the range of 0-100%. These features place our product in the centre of the HCL (Human Centric Light) The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.

The Tuya system is integrated with the Smart Things, Smart Life and Smart Home system.

Additionally, it is possible to control Tuya devices through compatible voice applications. Voice control by: Amazon Alexa, Google Assistant, Yandex Alice.



This product offers the benefit of controlling the light with the use of smartphone from any place in the world via IoT TUYA system. The user can control not only the brightness in the range of 0-100% but also the colour temperature in the range between 2700K and 6500K. These features place our product in the centre of the HCL (Human Centric Light)



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



This product offers the benefit of controlling the light with the use of smartphone from any place in the world via IoT TUYA system. The user can control not only the brightness in the range of 0-100% but also the colour temperature in the range between 2700K and 6500K. These features place our product in the centre of the HCL (Human Centric Light)



Ambient temperature suitable for operation

Name of the parameter	Value
Klasyfikacja GPC	10006896
Jednostka gsl	szt
Zawartość netto produktu	1
Wattage	12V:<180W, 24V:<360 W
Warranty (years)	5
PWM frequency	1,95 KHz
RF frequency	2.4 GHz
RF distance	≤20 m
Output current	≤15 A

Name of the parameter	Value
Remote included	No
Output types	RGB CCT
Output channels	5
Supply voltage range and voltage type	DC12V-24V
Ambient temperature suitable for operation	-20 ÷ 60 °C
Length	70 mm
Width	40 mm
Height	20 mm
Product weight with packaging (g)	80 g
Product code	201231

Pre-packaging



Width [mm] **54**
Height [mm] **30**
Length [mm] **90**

Cumulative packaging



Number of pieces **100**
Width [mm] **48**
Height [mm] **18**
Length [mm] **22**
Weight [kg] **5,8**
Type of carton box **Cardboard**