


LED line PRIME Panel Backlit 34W CCT 4760lm UGR<19 620x620



The Backlit LED line PRIME panel is an ideal solution for the German market, where energy-saving and efficient light sources are needed for lighting projects. Its high lighting quality and low glare make it an excellent choice for office, retail, educational spaces and other places where comfort and lighting quality play a key role.

The luminaire has a backlit design, which means placing the LEDs on the back of the body to ensure high and uniform light output.

Equipped with a yellow free type diffuser, it does not yellow, and the micro-prismatic texture provides high light transmittance while reducing glare (UGR<19 rating), which is beneficial for user comfort.

Lifud's robust power supply is a guarantee of trouble-free operation, but also a long life of the luminaire.

The luminaire provides high performance: an impressive luminous flux of 4760 lm and an efficiency of 140 lm/W. The luminaires are available with a 5-year warranty, giving you peace of mind that your investment in the panel is covered by the manufacturer's solid support and demonstrating confidence in the durability and reliability of the luminaires offered.

Backlit LED line PRIME panel is an excellent solution also because of the possibility of multiple mounting options. It allows flush mounting in modular suspended ceilings. It will also work well in cardboard/gypsum ceilings, using special brackets. Surface mounting is possible with a frame.

The luminaire is ENEC certified, confirming its high quality and compliance with European safety standards.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its esthetic appearance for many years.



The product has the prestigious ENEC certification, which confirms its superior quality, safety and compliance with stringent European standards.



This product has been contrued with the use of high quality LIFUD branded driver.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity

Parameter	Value
Luminous efficacy	140 lm/W
Power	34 W
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	4760 lm
Correlated colour temperature	3000-5000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Beam angle	90 °
Material (cover)	polystyrene
Material (housing)	aluminum
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9

Parameter	Value
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1
Height	30 mm
EPREL ID	1 947 263
Date of first placement on the market	2024-06-24 04:43:10
Form of the product (EPREL)	Source Out
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	Yes
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	No
Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	19
Total luminous flux (EPREL)	5 550
On-mode power Pon (EPREL)	32
Useful luminous flux Φuse (EPREL)	5 550
Beam angle in degrees (EPREL)	120

Single packaging



Width	35 mm
Height	640 mm
Length	630 mm
Weight	2,6 kg
	1

Bulk packaging



Outer box quantity	5 pcs.
	5
Width	200 mm
	640
Length	650 mm
Weight	12,7 kg
Volume	0,085 m3

Europallet

