

code: 207806 EAN: 5905378207806

Linear luminaire EXECULINE 30W
4000K 3750lm 120 cm IP20 96° white
PRIME



The EXECULINE linear luminaire is a modern luminaire with an elegant, minimalist design, ideal for use in offices, commercial and industrial spaces. With a wattage of 30W and a luminous flux of 3900 lm, it provides effective white (4000K) lighting with an efficiency of 130 lm/W.

The luminaire is 120 cm long, 3.5 cm wide and 6 cm high, making it slim and stylish. The product has a high colour rendering index of Ra80 and a luminous angle of 96°, ensuring even light dispersion. With an IP20 rating, it is designed for indoor use.

The housing is made of high-quality aluminium, which ensures durability and lightweight construction, while the diffusing material diffuser ensures even and gentle illumination. It provides a long life of 50,000 hours (L70B50) and a PF power factor of 0.9.

It is the ideal solution for those who value aesthetics, functionality and durability in the lighting of interior spaces.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Lifespan




Beam angle




Ambient temperature suitable for operation

| Parameter | Value |
|---------------------------------------|-------------|
| Luminous efficacy | 130 lm/W |
| Power | 30 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | D |
| Luminous flux | 3900 lm |
| Correlated colour temperature | 4000 K |
| Colour consistency in McAdam ellipses | ≤3 |
| Standby power | 0 |
| IP protection rating | 20 |
| Warranty (years) | 5 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 50 000 |
| Mounting type | mixed |
| Supply voltage range and voltage type | 220-240 VAC |
| Frequency of the supply voltage | 50/60Hz |
| Colour rendering index Ra | 80 |
| The lumen maintenance factor | 96 % |
| Beam angle | 96 ° |
| Power Factor | 0,9 |

| Parameter | Value |
|--|--------------------|
| Ambient temperature suitable for operation | -15÷45 °C |
| For indoor use | Inside |
| IEC protection class | I |
| Lamp's warm-up time to 60% | 1 |
| Length | 1200 mm |
| Width | 35 mm |
| Height | 60 mm |
| EPREL ID | 2 052 993 |
| Form of the product (EPREL) | Source Out |
| Angle for useful luminous flux (EPREL) | Sphere 360 degrees |
| Is the product equipped with an integrated light source? (EPREL) | Yes |
| Non-directional or directional light source (EPREL) | NDLS |
| Mains or non- mains light source (EPREL) | NMLS |
| Connected light source (EPREL) | No |
| Colour-tuneable light source (EPREL) | No |
| Total luminous flux (EPREL) | 2 300 |
| On-mode power Pon (EPREL) | 14 |
| Useful luminous flux Φuse (EPREL) | 2 300 |
| Beam angle in degrees (EPREL) | 120 |




Single packaging



| | |
|--------|---------|
| Width | 40 mm |
| Height | 80 mm |
| Length | 1250 mm |
| Weight | 1,4 kg |
| | 1 |

Bulk packaging



| | |
|--------------------|---------|
| Outer box quantity | 10 pcs. |
| | 10 |
| Width | 180 mm |
| | 220 |
| Length | 1260 mm |
| Weight | 15 kg |
| Volume | 0,05 m3 |

Europallet

