



Product code: 240058 EAN: 5901583240058

LED line® strip 150 SMD 12V green 2,4W



Product description

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



IP protection rating



Lifespan



Voltage range and voltage type



LED type



Beam angle



Laminate (thickness)



Compatible dimmer type



Cutting section



LED quantity (1m)



Number of on/off cycles



Type of adhesive tape



IEC protection class




Ambient temperature suitable for operation



Name of the parameter	Value
Colour of the light	Green
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (lm)	2,4 W
Wavelength	520nm
Current (lm)	0,2
Supply voltage range and voltage type	12 DC


Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	30
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	7,73
Product code	240058

Luminous [cd/klm]



C0 - C180 **C90 - C270**


Cumulative packaging



Number of pieces

100

Europallet



Number of pieces

960

Bulk quantity

24

Pallet height [mm]

984

Quantity in 1 layer

8

Number of layers

3