


Product code: 240133 EAN: 5901583240133

## LED line® strip 150 SMD 12V yellow 2,4W IP65



### Product description

Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years. This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre. Manufacturer issues a 3-year warranty for this product.




	Manufacturer issues a 3-year warranty for this product.		Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.
	Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.		This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.
	Lifespan		Voltage range and voltage type
			Beam angle
	LED type		Compatible dimmer type
	Laminate (thickness)		LED quantity (1m)
	Cutting section		Type of adhesive tape
	Number of on/off cycles		Ambient temperature suitable for operation
	IEC protection class		

Name of the parameter	Value
Colour of the light	Yellow
Warranty (years)	3
Minimum purchase quantity	5
Lifetime L70B50	30000
Wattage (lm)	2,4 W
Wavelength	590nm
Current (lm)	0,2
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	30
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
LED strip (upper) IP protection rating	65
LED strip (bottom) IP protection rating	20
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	13,58
Product code	240133

## Luminous [cd/klm]



## Cumulative packaging



Number of pieces

**100**

## Europallet



Number of pieces

**960**

Bulk quantity

**24**

Pallet height [mm]

**984**

Quantity in 1 layer

**8**

Number of layers

**3**