

Product code: 240140 EAN: 5901583240140

LED line® strip 150 SMD 12V RGB 7,2W

Product description

This LED strip produces light from RGB colour palette. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



qIş

٩Į٥

¢₫\$



Manufacturer issues a 5-year warranty for this product.

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



<u>کمہ</u> 120 IP protection rating

Voltage range and voltage type

Beam angle

Compatible dimmer type



LED quantity (1m)

Type of adhesive tape



Ambient temperature suitable for operation



This LED strip produces light from RGB colour palette.



(?)

LED type

Lifespan

Laminate (thickness)




РСВ

Cutting section



Number of on/off cycles






LE line

Name of the parameter	Value
Colour of the light	RGB
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (1m)	7,2 W
Wavelength	620, 520, 465nm
Current (lm)	0,6
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD5050
Not dimmable	ТАК
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	30
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Ambient temperature suitable for operation	`-20 ÷ 45 ℃
For indoor use	YES
IEC protection class	Ш
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	10 mm
Height	2,5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	9,53
Product code	240140

LE line


Luminous [cd/klm]



Cumulative packaging

Number of pieces
Width [mm]
Height [mm]
Length [mm]
Weight [kg]
Volume [m3]

100
340
280
440
0,13
0,042



Pallet height [mm]

Quantity in 1 layer

Number of layers

```
2400
60
300
300
1800
6
10
```