


Product code: 244056 EAN: 5901583244056

## LED line® strip 70 SMD 12V 6500K 18W WIDE BEAM 160°



### Product description

It is a solution for the needs of most demanding customers. Using LED line® WIDEBEAM strip, featured by a wide beam angle of 160°, the user will achieve even and constant illumination with only 6 cm distance between LED and illuminated surface. Manufacturer issues a 5-year warranty for this product. The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light.



Manufacturer issues a 5-year warranty for this product.



Using LED line® WIDEBEAM strip, featured by a wide beam angle of 160°, the user will achieve even and constant illumination with only 6 cm distance between LED and illuminated surface.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



IP protection rating



Lifespan



Voltage range and voltage type



Beam angle



LED type



Compatible dimmer type



Laminate (thickness)



LED quantity (lm)



Cutting section



Type of adhesive tape



Number of on/off cycles



Ambient temperature suitable for operation




IEC protection class


Name of the parameter	Value
Colour of the light	White
Correlated colour temperature	6500 K
Luminous efficacy	70 lm/W
Energy efficiency class 2019/2015	G
Colour consistency in McAdam ellipses	≤3
IP protection rating	20
Warranty (years)	5
Dimmable function	Yes
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (lm)	18 W
Luminous flux (lm)	1260lm
Current (lm)	1,5
Supply voltage range and voltage type	12 DC
Colour rendering index Ra	80

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	96
Beam angle	160 °
LED type	SMD6060
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	14
Cutting section	7
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	10 mm
Height	4 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	8,93
EPREL ID	632036
Date of first placement on the market	01.05.2017
Energy class	A
Form of the product (EPREL)	Dotyczy 7cm taśmy
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	NMLS
Chromaticity coordinates x i y (EPREL)	0.314 0.324
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	6
Total luminous flux (EPREL)	88
On-mode power P <sub>on</sub> (EPREL)	1
Useful luminous flux Φ <sub>use</sub> (EPREL)	88
Beam angle in degrees (EPREL)	160
Product code	244056

## Luminous [cd/klm]




### Cumulative packaging



Number of pieces

**100**

### Europallet



Number of pieces

**960**

Bulk quantity

**24**

Quantity in 1 layer

**8**

Number of layers

**3**