


Product code: 244216 EAN: 5901583244216

LED line® strip 300 SMD 12V 6500K 7,2W SIDE VIEW



Product description

It is a solution for the needs of most demanding customers. It is a model of LED strip which provides illumination at the 90 degrees angle (edge light), which allows for a wide range of applications in the advertising industry. Manufacturer issues a 5-year warranty for this product. The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



It is a model of LED strip which provides illumination at the 90 degrees angle (edge light), which allows for a wide range of applications in the advertising industry.



Manufacturer issues a 5-year warranty for this product.



Lifespan



LED type



Laminate (thickness)



Cutting section



Number of on/off cycles



IEC protection class



The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



IP protection rating



Voltage range and voltage type



Beam angle



Compatible dimmer type



LED quantity (1m)



Type of adhesive tape




Ambient temperature suitable for operation

Name of the parameter	Value
Colour of the light	White
Correlated colour temperature	6500 K
Luminous efficacy	76 lm/W
Energy efficiency class 2019/2015	G
Colour consistency in McAdam ellipses	≤3
IP protection rating	20
Warranty (years)	5
Dimmable function	Yes
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (lm)	7,2 W
Luminous flux (lm)	550lm
Current (lm)	0,6
Supply voltage range and voltage type	12 DC
Colour rendering index Ra	80

Name of the parameter	Value
Metres per roll	5
The lumen maintenance factor	96
Beam angle	120 °
LED type	SMD3014
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Cutting section	5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	6,98
EPREL ID	632039
Date of first placement on the market	01.10.2017
Energy class	A+
Form of the product (EPREL)	Dotyczy 50cm taśmy
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	NMLS
Chromaticity coordinates x i y (EPREL)	0.314 0.324
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	8
Total luminous flux (EPREL)	275
On-mode power P _{on} (EPREL)	3
Useful luminous flux Φ _{use} (EPREL)	275
Beam angle in degrees (EPREL)	120
Product code	244216

Luminous [cd/klm]



Cumulative packaging



Number of pieces

100

Europallet



Number of pieces

960

Bulk quantity

24

Quantity in 1 layer

8

Number of layers

3