


Product code: 246500 EAN: 5901583246500



















LED line® strip 210 SMD 12V RGB 10W TWIST



Product description

It is a solution for the needs of most demanding customers. LED line® TWIST strip can be bent in any direction without any risk of any damage to the laminate. This LED strip produces light from RGB colour palette. Manufacturer issues a 5-year warranty for this product. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.




	Manufacturer issues a 5-year warranty for this product.		This LED strip produces light from RGB colour palette.
	LED line® TWIST strip can be bent in any direction without any risk of any damage to the laminate.		Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.
	IP protection rating		Lifespan
	Voltage range and voltage type		
	Beam angle		LED type
	Compatible dimmer type		Laminate (thickness)
	LED quantity (1m)		Cutting section
	Type of adhesive tape		Number of on/off cycles
	Ambient temperature suitable for operation		IEC protection class


Name of the parameter	Value
Colour of the light	RGB
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50000
Wattage (lm)	10 W
Wavelength	620, 520, 465nm
Current (lm)	0,83
Supply voltage range and voltage type	12 DC

Name of the parameter	Value
Metres per roll	5
Beam angle	120 °
LED type	SMD5050
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	42
Cutting section	7,1
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	12 mm
Height	2,5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	11,03
Product code	246500

Luminous [cd/klm]




Cumulative packaging



Number of pieces	100
Width [mm]	340
Height [mm]	280
Length [mm]	440
Weight [kg]	0,12
Volume [m3]	0,042

Europallet



Number of pieces	960
Bulk quantity	24
Weight [kg]	2,88
Weight [kg]	2,88
Pallet height [mm]	984
Quantity in 1 layer	8
Number of layers	3