

PRODUCT DATASHEET

WORK VAL H-STAND 50 W 4000 K IP65

WORKLIGHT VALUE H-STAND | Robust, portable worklight



AREAS OF APPLICATION

- Renovation
- Garages
- Basement
- Workshops

PRODUCT BENEFITS

- Energy savings of up to 80% compared to halogen lamp worklights
- Semi-frosted, tempered glass cover for uniform illumination
- 3 years guarantee

PRODUCT FEATURES

- Compact ground stand
- Die-cast aluminum housing with PC front cover
- Type of protection, luminaire head and housing: IP65, Type of protection, plug: IP44
- Quick-release fastener for adjustment of luminaire head angle
- 2 m cable with type E/F plug



TECHNICAL DATA

Electrical data

Nominal wattage	50.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Power factor λ	>0.90
Total harmonic distortion	< 20 %


Photometrical data

Color temperature	4000 K
Color rendering index Ra	<80
Light color (designation)	Cool White
Luminous flux	4500 lm
Luminous efficacy	90 lm/W
Standard deviation of color matching	<6 sdc _m

Light technical data

Beam angle	110 °
------------	-------

— Dimensions & weight



Length	264.0 mm
Width	270.0 mm
Height	375.0 mm
Product weight	2270.00 g
Cable length	2000 mm

Colors & materials

Product color	Black
---------------	-------

Housing color	Black
Body material	Aluminum
Cover material	Glass

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
----------------------------------	--------------

Lifespan

Number of switching cycles	10000
Lifespan L70/B50 at 25 °C	30000 h

Additional product data

Mounting type	Standing
Mounting location	Floor

Capabilities

Dimmable	No
Type of connection	Protective contact Plug type
LED module replaceable	Not replaceable

Certificates & standards

Type of protection	IP65 ¹⁾
Protection class	I
Protection class IK (shock resistance)	IK06
Glow Wire Test according to IEC 60695-2-12	650 °C
Photobiological safety group EN62778	RG 1
Luminaire with limited surface temperature, class "D"	No
Standards	CE/CB/EAC/RoHS

¹⁾ Luminaire head and housing IP65, plug IP44

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075322493	Folding carton box 1	278 mm x 286 mm x 387 mm	2483.00 g	30.77 dm ³
4058075322509	Shipping carton box 2	572 mm x 300 mm x 405 mm	6082.00 g	69.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.