



















Technical sheet

Metal industrial luminare with IP65

MODUS MEGA LED 1220mm, wide beam, 2x LED, 840, PC cover, pendant, IK10, 2100mA non-dimmable, with gear box

Code: MEGALW2M4PCV1/2100ND

EAN: 8595073714456

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	High bay luminaire	Effective luminous flux (Im):	14500
System power (W):	92	Luminaire efficacy (lm/W):	158
Rated lifetime L70/B50 (h):	100000	Rated lifetime L80/B50 (h):	80000
Degree of protection (IP):	IP65	Mounting method:	Pendant
Color housing:	White		
Impact strength:	IK10		
Ball-proof:	Yes	Material housing:	Steel
Light source included:	Yes	Fire resistance D:	Yes
Rated ambient temperature (°C):	-25+45	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast
Light source type:	1991200184003	Energy efficiency class:	С

Optical system

Optical system:	PC	Reflector:	High-gloss
Light sharing:	Symmetric	Material reflector:	Aluminium
Radiation angle:	Extreme wide beam >80°		

Dimensions

Length (mm):	1224	Width (mm):	197
Height/depth (mm):	90	Built-in length (mm):	940
Built-in width (mm):	140	Size version:	М
Weight (kg):	6		

Electrical values

Protection class:	II	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220240
Control gear included:	Yes	No dim function:	Yes
Indoor use only:	Yes		