



LED waterproof light fitting

MODUS PL 10000, wide body 1575mm, LED 840 , body PE, opal PC cover, IP65, driver 2100mA

Code: PL10000L2W4ND

EAN: 8596099001995

This product contains a light source with energy efficiency class C



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	10200
System power (W):	68	Luminaire efficacy (lm/W):	150
Rated lifetime L80/B50 (h):	80000	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes		
Material housing:	Plastic		
Light source included:	Yes	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Rated ambient temperature (°C):	-10...+45
Suitable for ceiling mounting:	Yes	Made in Czech republic:	Yes

Light source

Light source type:	LED	Color temperature (K):	4000
Color rendering index CRI:	80-89	Replaceability:	Replaceable light source by professional, replaceable ballast
Light source type:	1990660184005	Energy efficiency class:	C

Optical system

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Dimensions

Length (mm):	1575	Width (mm):	135
Height/depth (mm):	100	Built-in length (mm):	1100
Size version:	L	Weight (kg):	2,8

Electrical values

Protection class:	I	Voltage type:	AC
Type of control gear:	LED operating device current-controlled	Nominal voltage (V):	220...240
Control gear included:	Yes	No dim function:	Yes
Indoor use only:	Yes		