

Type: **DILM150-XHIA11**

Article No.: **283463**

Sales text **Contactors, aux.contact, 2-pole**




With positively driven contacts; except XHIV and XHICV

### Ordering information

Connection technique			Screw terminals
Description			2 pole
Conventional thermal current $I_{th} = I_e$ AC-1 at 50 °C			
Open	$I_{th} = I_e$	A	16
Contacts			
N/O = Normally open, N/O E = Normally open (early make contact)			1 N/O
N/C = Normally closed N/C L = Normally closed (late break contact)			1 N/C
Can be combined with basic unit			DILM40... DILM50... DILM65... DILM72... DILM80... DILM95... DILM115... DILM150... DILM170... DILMP63 DILMP80 DILMP125

---

## Contact sequence



---

## Notes concerning the product group

- Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L, within the auxiliary contact modules (not N/O (early make) and N/C (late break) contacts) and for the built-in auxiliary contacts of the DILM7 – DILM32
- Auxiliary break contact can be used as mirror contact to IEC/EN 60947-4-1 Annex F (not N/C (late break) contact)
- No auxiliary contacts can be fitted between 2 contactors.

---

Moeller GmbH, Hein-Moeller-Str. 7-11, D-53115 Bonn  
E-Mail: [catalog@moeller.net](mailto:catalog@moeller.net), Internet: [www.moeller.net](http://www.moeller.net), <http://catalog.moeller.net>  
HPL-C2007G V2.1 © 2007 by Moeller GmbH