


### U-Clamp

with pressure trough

BW 14

EAN Code: 4013339056101  
Smallest packaging unit: 100 pcs.

the photorealistic images are to be considered as reference images



### Article Description

U-clamp, for angle irons 40x40x4-6 mm, for 1 cable, Ø 10-14 mm, steel, hot dip galvanised DIN EN ISO 1461, with steel pressure trough

### Additional Price Information

Article group	N08
quantity unit	pcs.

### Weight

Weight per quantity unit	42 g / pcs.
Weight in kg per 100	4,18 kg / 100pcs.

# Technical Datasheet

## U-clamps

BW 14

the photorealistic images are to be considered as reference images

### Physical Article Dimensions

Height	18.00 mm
Width	100.00 mm
Depth/length	29.00 mm

### Packing Dimension

<b>100 pieces = 1 carton</b>		✓ VP1-smallest packaging unit ( PU)		✓ VP1-preferred PU	
Lenght	250 mm	Width	250 mm	Height	120.00 mm
Volume	0,008 m <sup>3</sup>	Gross weight	4,56 kg		
Min. quantity	100.00 pcs.	Max. Quantity	100.00 pcs.		

<b>6000 pieces = 1 pallet</b>					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	289 kg	Volume	0,960 m <sup>3</sup>		
Min. Quantity	6.000.00 pcs.	Max. Quantity	6.000.00 pcs.		

### Tender Text

U-clamp, for angle iron, with pressure trough and M 6 pivot bolt with multiple drive, can be used on isosceles and isosceles angle steel and U-iron.  
 Universal-Counter Trough GWU ... / GWS ... please order separately.  
 Used for: equal and unequal-legged angle steel and U-iron with a maximum leg length of 40 mm and a thickness of 4 - 6 mm  
 Dimensions (approx. dimensions)  
 Assignment : 1 cable  
 for cable-Ø : 10 - 14 mm  
 Material bracket : steel, hot-dip galvanised in accordance with DIN EN ISO 1461  
 Material pressure tray : steel, strip galvanised to DIN EN 10346  
 NIEDAX model no. : BW 14  
 EP material \_\_\_\_\_ EP wage \_\_\_\_\_  
 Unit price/piece

### Safety & Environment

REACH Date	05.11.2025
REACH Info	Conformable
RoHS Info	Conformable

### Origin & International Trade

Country of origin	DE
Customs tariff number	73269098