

High protection

Easy to install. Fitting in any environment.

OBO Aluminium conduits.



- Less weight
- High resistance against compression and impact
- Corrosion resistant
- M16 – M63
- Accessories: Bends and couplings

OBO Aluminium conduits


Aluminium pipe, without thread

Type	Dim. D mm	Dim. L mm	Dim. t mm	Pack. m	Weight kg/100 m	Item No.
S16W ALU	16	3000	1.2	30	15,067	2046 00 2
S20W ALU	20	3000	1.2	30	19,134	2046 00 3
S25W ALU	25	3000	1.3	30	26,134	2046 00 4
S32W ALU	32	3000	1.3	30	33,834	2046 00 5
S40W ALU	40	3000	1.4	15	45,800	2046 00 6
S50W ALU	50	3000	1.4	15	57,700	2046 00 7
S63W ALU	63	3000	1.7	15	88,334	2046 00 8

Alu Aluminium

price/100 m

Electrical installation pipe without threaded ends to EN 61386-1 for mechanical protection of cables. With burr-free inner wall.




Aluminium pipe bend, without thread

Type	Dim. A mm	Dim. B mm	Dim. D mm	Dim. I mm	Dim. R mm	Dim. t mm	Pack. pcs	Weight kg/100 pcs.	Item No.
SB16W ALU	78	151	16	28	64	1.2	15	2,350	2046 01 2
SB20W ALU	80	171	20	30	80	1.2	25	5,500	2046 01 3
SB25W ALU	93	209	25	38	102.5	1.3	25	9,000	2046 01 4
SB32W ALU	105	253	32	40	131	1.3	20	14,100	2046 01 5
SB40W ALU	115	302	40	50	165	1.4	15	22,400	2046 01 6
SB50W ALU	128	360	50	63	205	1.4	5	35,400	2046 01 7
SB63W ALU	135	425	63	70	256.5	1.7	3	59,500	2046 01 8

Alu Aluminium

/100 pc.

90° bend with moulded sleeves, for electrical installation pipes according to EN 61386-1. With burr-free inner wall.




Aluminium sleeve, without thread

Type	Dim. M mm	Dim. L mm	Dim. D mm	Dim. t mm	Pack. pcs	Weight kg/100 pcs.	Item No.
SV16W ALU	16	40	18.6	1.2	50	0,700	2046 02 2
SV20W ALU	22.6	20.2	50	25	50	1,300	2046 02 3
SV25W ALU	27.6	25.2	60	30	50	1,900	2046 02 4
SV32W ALU	34.6	32.2	70	35	50	2,400	2046 02 5
SV40W ALU	43	40.2	70	35	20	4,000	2046 02 6
SV50W ALU	53	50.2	90	45	20	6,100	2046 02 7
SV63W ALU	66.2	63.2	110	55	20	9,000	2046 02 8

Alu Aluminium

/100 pc.


Accessory part: plug-in sleeve for the connections between electrical installation pipes. With burr-free inner wall.



Select list
Conduit size
(External diameter in mm)

Cable cross section (mm²)

Number of cables	1,5	2,5	4	6	10	16	25	35	50	70	95
1	M16	M16	M16	M16	M16	M16	M20	M25	M25	M32	M32
2	M16	M16	M16	M16	M20	M25	M32	M32	M40	M40	M50
3	M16	M16	M20	M20	M25	M32	M32	M40	M50	M50	M63
4	M16	M16	M20	M20	M32	M32	M40	M40	M50	M63	M63
5	M16	M20	M20	M25	M32	M32	M40	M50	M50	M63	-



OBO Bettermann India Pvt. Ltd.

A51, SIPCOT Industrial Growth Centre,
Oragadam, Sriperumudur Taluk,
Kancheepuram – 602105,
Tamilnadu, India.

Email: sales@oboindia.com
Tel.: +91 44 71033900/901/902
Fax +91 44 71033999

