



E5CC-QX2DBM-000

Temperature controller, 1/16DIN (48 x 48mm), 12 VDC pulse output, 2 x auxiliary relay outputs, universal input type, 24 V AC/DC

Műszaki jellemzők


Size	1/16 DIN (48 x 48 mm)
Functions	ON/OFF control, PID control
Number of control loops	1
Temperature input type	B, C (WRe5-26), E, J, JPt100, K, L, N, P (PLII), Pt100, R, S, T, U
Linear analog input type	0 to 10 V, 0 to 20 mA, 0 to 5 V, 1 to 5 V, 4 to 20 mA
Temperature range	-200-2300 °C
Number of event inputs	0
Number of alarm outputs	2
Supply voltage AC	20.4-26.4 V
Supply voltage DC	20.4-26.4 V
Control output	Voltage pulse
Terminal type	Push-in

Kiegészítők



E58-CIFQ2

E5CB & E5CC and E5EC* accessory, quick link programming cable, allows direct USB connection without requirement for communications card or power supply. Also the display will be powered (CX-Thermo v4.4 is needed). *For E5EC front connection.



EST2-2C-MV4

CX-Thermo, direct 1 to 1 connecting software (1 to several if same TC type), for programming and monitoring E5_N (version 5 & 6), E5ZN and CelciuX (EJ1)


CAD Könyvtár



Digital Temperature Controllers

Brosúra

EN PDF 4 MB



E5CC-B

Felhasználói kézikönyv

EN PDF 3 MB



E5CN-E5CC Conversion File

Szoftver

EN ZIP 600 KB



E5_C safety_precautions

Adatlap

EN PDF 2 MB



E5_C/E5_C-T Digital Temperature Controller

Adatlap

EN PDF 40 MB



EAC Mark removal

Kivonási megjegyzés

EN PDF 200 KB



Panel Building

Brosúra

EN PDF 3 MB



Thermac Temperature Simulation

Szoftver

EN ZIP 20 MB