

64611 HLX

Low-voltage halogen lamps without reflector



Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



Product datasheet

Technical data

Product information

Order reference	64611 HLX
-----------------	-----------


Electrical data

Nominal voltage	12.0 V
Nominal wattage	50.00 W

Photometrical data

Color temperature	3250 K
Nominal luminous flux	1350 lm

Dimensions & weight



Diameter	11.5 mm
Length	44.0 mm
Light center length (LCL)	30.0 mm
Filament length	3.30 mm
Illuminated field	3.3*1.6 mm ²
Filament diameter	1.6 mm

Lifespan

Lifespan	100 h
----------	-------

Additional product data

Base (standard designation)	G6.35
Minimum diameter of lamp enclosure	12 mm

Capabilities

Product datasheet

Dimmable	Yes
Burning position	s90
Application	Other

Certificates & standards

EEI – Energy Label	B
---------------------------	---

Country specific categorizations

Order reference	64611 HLX
------------------------	-----------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321107091	OSRH64611HLX	-	-	-
4008321107091	OSRH64611HLX	-	-	-

Product datasheet



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321107091	64611 HLX	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm ³	4.50 g
4008321107107	64611 HLX	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm ³	221.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.