

PRODUCT DATASHEET

HALOLUX T 40 W 230 V E14

HALOLUX® T | Halogen lamps for refrigerators



Areas of application

- Domestic refrigerators

Product benefits

- Compact dimensions
- UV filter
- Contains no mercury

Product features

- Average life: 2,000 h
- 100 % dimmable


TECHNICAL DATA

Electrical data

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal voltage	230.00 V
Nominal current	0.17 A
Power factor λ	1.00

Photometrical data

Luminous flux	490 lm
Luminous efficacy	12 lm/W
Lumen main.fact.at end of nom.life time	0.80
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	100
Light color	1027



Light technical data

Warm-up time (60 %)	0.00 s
Starting time	0.0 s

Dimensions & Weight

Overall length	80.00 mm
Light center length (LCL)	55,0 mm
Diameter	26,0 mm
Maximum diameter	26 mm
Product weight	12.9 g

Lifespan

Nominal lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Tube

Capabilities

Dimmable	Yes
Burning position	Any

Certificates & Standards

Energy efficiency class	D
Energy consumption	40.00 kWh/1000h

Country-specific categorizations

ILCOS	HSGST/C/UB-40-230-E14-55
Order reference	64861 T ECO

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E14
Length	80.00 mm
Height	26,0 mm
Width	26,0 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300363707	Folding box 1	111 mm x 42 mm x 42 mm	28.10 g	0.20 dm ³
4050300363714	Shipping box 15	225 mm x 125 mm x 140 mm	520.50 g	3.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.