
Product datasheet

DULUX T/E PLUS 42 W/830

OSRAM DULUX T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation



Product datasheet

Technical data

Photometrical data

Color rendering index Ra	≥80
--------------------------	-----

Lifespan

Nominal lamp life time	20000 h
------------------------	---------

Additional product data

Appropriate disposal acc. to WEEE	Yes
-----------------------------------	-----


Certificates & standards

Energy efficiency class	G
-------------------------	---

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300425641
Declaration No. in SCIP database	In work


Light Distribution



FL_830

Equipment / Accessories

- Suitable for operation on electronic control gear



SINGLE LAMP WITH QUICKTRONIC QT-DE

Product datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300425641	DULUX T/E PLUS 42 W/830	Shipping carton box 10 Pieces Folding carton box	218 mm x 191 mm x 140 mm	5.83 dm ³	999.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to
▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

DULUX T/E PLUS 42 W/830

OSRAM DULUX T/E PLUS | CFLni, 3 tubes, with 4-pin base for ECG operation

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Power factor λ [PIM]	Luminous flux at 25 °C
DULUX T/E PLUS 42 W/830	QTi DALI-T/E 1x18-57 DIM	4008321060808	0.21 A	47.00 W	0.99	3200 lm
	QTi DALI-T/E 2x18-42 DIM	4008321060822	0.39 A	90.00 W	0.99	3200 lm
	QTi-T/E 1x18-57 DIM	4008321060860	0.21 A	47.00 W	0.99	3200 lm
	QTi-T/E 2x18-42 DIM	4008321060846	0.39 A	90.00 W	0.99	3200 lm
	QT-M 2x26-42/220-240 S	4008321110022	0.39 A	92.00 W	0.97	3200 lm
	QTP-M 1x26-42	4008321329134	0.20 A	46.00 W	0.97	3200 lm
	QTP-M 2x26-32	4008321329158	0.20 A	46.00 W	0.97	3200 lm
	QTP-T/E 1x26-42, (2x26)	4008321537089	0.20 A	45.00 W	0.95	3200 lm

Product name	Product name ECG	EAN	Number of lighting outlets
DULUX T/E PLUS 42 W/830	QTi DALI-T/E 1x18-57 DIM	4008321060808	1
	QTi DALI-T/E 2x18-42 DIM	4008321060822	2
	QTi-T/E 1x18-57 DIM	4008321060860	1
	QTi-T/E 2x18-42 DIM	4008321060846	2
	QT-M 2x26-42/220-240 S	4008321110022	2
	QTP-M 1x26-42	4008321329134	1
	QTP-M 2x26-32	4008321329158	1

Product datasheet

Product name	Product name ECG	EAN	Number of lighting outlets
	QTP-T/E 1x26-42, (2x26)	4008321537089	1