

PRODUCT DATASHEET IVIOS LED III 10 W WT

IVIOS LED III | Spotlights and downlights



PRODUCT BENEFITS

- Pleasant homogenous light
- Long lifetime thanks to LED technology
- Low installation depth

PRODUCT FEATURES

- Recessed LED downlight
- Type of protection: IP44
- Solid aluminum housing in white
- Beam angle: 90°
- Color temperature: 3,000 K
- Lifetime: up to 25,000 h
- Protection class: II
- Dimmable (with suitable Phase-cut dimmers)



TECHNICAL DATA

Electrical data

Operating mode	ECG Dimmable
Nominal wattage	10 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Luminous flux	600 lm
Color rendering index Ra	>80

Dimensions & weight

Length	110.0 mm
Diameter	110.0 mm
Height	43.0 mm
Product weight	330.00 g

Colors & materials

Product color	White
----------------------	-------

Capabilities

Type of installation	Recessed
Adjustable	No
Dimmable	Yes

Certificates & standards

Protection class	II
Type of protection	IP44
Standards	CE

EQUIPMENT / ACCESSORIES

- External control gear included (cabled on the secondary side)

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899904071	IVIOS LED III 10 W WT	Folding carton box 1	136 mm x 91 mm x 237 mm	2.93 dm ³	437.00 g
4052899904132	IVIOS LED III 10 W WT	Shipping carton box 4	289 mm x 199 mm x 268 mm	15.41 dm ³	2274.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.