

# PRODUCT DATASHEET CLA A FR 100 13 W/2700 K E27

LED Antibacterial Classic | Consumer Antibacterial Led Lamp With Classic Bulb



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

#### **Product benefits**

- Very low energy consumption
- Can be easily fitted instead of ordinary light bulbs

#### **Product features**

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering ( $R_a \ge 80$ ) and color stability throughout the life of the lamp






## **TECHNICAL DATA**

## Electrical data

Nominal wattage	13 W
Construction wattage	13.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	100 W
Nominal current	100 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Total harmonic distortion	150 %
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	≤1
Stroboscope effect metric (SVM)	≤0.9




# Light technical data

Beam angle 200 °
------------------

Starting time	< 0.5 s
Rated beam angle (half peak value)	200.00 °

# **Dimensions & Weight**



Overall length	118.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	43.00 g

# Lifespan

Nominal lamp life time	10000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

# Additional product data

Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

# **Capabilities**

B	
Dimmable	No

## Certificates & Standards

Energy efficiency class	F <sup>1)</sup>
Energy consumption	13.00 kWh/1000h
Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

## **Country-specific categorizations**

Order reference	LCCLA100 13W/82
Energy labellling regulation data acc EU 2019/2015	
Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00 W
Networked standby power for CLS	0.00 W
Claim of equivalent power	Yes
Length	118.00 mm
Height	60.00 mm
Width	60.00 mm
Chromaticity coordinate x	0,4578
Chromaticity coordinate y	0,4101
R9 Colour rendering index	0.00
Beam angle	SPHERE_360
Survival factor	0.5
Displacement factor	≥0.7
LED light source replaces a fluorescent light source	not applicable
EPREL ID	523299,734822
Model number	AC31141,AC36884

#### **DOWNLOAD DATA**

	DOWNLOAD DATA
PDF	Declarations of conformity EC Declaration of Conformity CLA Non Dim AC31141-56 AC31177-9 AC34531-3
	IES file (IES) LCCLA100 13W 827

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075560833	Folding box 1	62 mm x 62 mm x 122 mm	55.00 g	0.47 dm³
4058075560840	Shipping box 10	319 mm x 133 mm x 138 mm	630.00 g	5.85 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.