



|                        |                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article#               | <b>413-6</b>                                                                                                                                                                                                                                                                                                                                                         |
| article description    | <b>CEE-flanged socket sloping (70x85mm) 16A 3p 6h IP44/IP54</b>                                                                                                                                                                                                                                                                                                      |
| description long       | CEE-flanged socket sloping (70x85mm) 16A 3p 6h IP44/IP54<br>housing material: PA6<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 6h<br>rated voltage/frequency: 200-250V~ / 50+60Hz<br>contacts: brass<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 70x85 mm / 50x65 mm<br>IP protection class: IP44/IP54 |
| GTIN (EAN)             | 9003399116070                                                                                                                                                                                                                                                                                                                                                        |
| country of origin      | AT                                                                                                                                                                                                                                                                                                                                                                   |
| customs number         | 85366990                                                                                                                                                                                                                                                                                                                                                             |
| net weight             | 0.109 kg                                                                                                                                                                                                                                                                                                                                                             |
| packaging quantity     | 10                                                                                                                                                                                                                                                                                                                                                                   |
| minimum order quantity | 10                                                                                                                                                                                                                                                                                                                                                                   |

|                                 |                       |
|---------------------------------|-----------------------|
| ETIM 9.0                        | EC001317              |
| IEC-ampereage                   | 16 A                  |
| Voltage according to EN 60309-2 | 230 V (50+60 Hz) blue |
| Number of poles                 | 3                     |
| Clock hour position             | 6 h                   |
| Identification colour           | Blue                  |
| Degree of protection (IP)       | IP44                  |
| Connection system               | Screwed terminal      |
| Angle of plug                   | Angled                |
| Material                        | Plastic               |
| Contact material                | CuZn                  |
| Surface treatment contacts      | Untreated             |
| Flange size vertical            | 85 mm                 |
| Drill hole distance vertical    | 65 mm                 |
| Flange size horizontal          | 70 mm                 |
| Drill hole distance horizontal  | 50 mm                 |

|                        |                       |
|------------------------|-----------------------|
| a                      | 70 mm                 |
| b                      | 85 mm                 |
| c                      | 50 mm                 |
| d                      | 65 mm                 |
| e                      | 38 mm                 |
| f                      | 47 mm                 |
| g                      | 51 mm                 |
| h                      | 61 mm                 |
| i                      | 5,5 mm                |
| j                      | 85 mm                 |
| k                      | 99 mm                 |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| wire solid             | 1-4 mm <sup>2</sup>   |
| contact screws         | 100 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |
| IK-code *)             | IK08                  |

method of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40°C and a relative humidity of 95%.



<https://www.pcelectric.at/shop/en/?func=detail&artnr=413-6>



\*) The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. PC Electric GmbH has therefore tested the IK-codes of these products in accordance with IEC 62262 and according to the test