

DATASHEET

RUNPOCAM RC2 -30 M + POWER REX

FOR PIPE INSPECTION FOR LONG DISTANCES UP TO 50 M

Item no.: 11138



VIDEO



RUNPOCAM RC2

Click here Video



Click here Productinformation

W-BOX | Sortimo KOMPATIBEL

CAMERA WITH REEL + MONITOR + CASE + INCLUDED ACCESSORIES:



A. RUNPOGLIDER with front thread B. Micro memory card 8 GB / adapter C. Connection thread set (blind cap, inside and outside connection thread) D. SYSTEMGLIDER RC2 E. Fishing hook F. Magnet fishing-set G. High-performance 320-lumen rechargeable LED lamp (protection rating IP 67) H. Dual USB charging adapter 12 V I. Flexible attachment 12 cm J. USB / Micro-USB charging cable 3 m K. USB charging cable for LED battery Lamp L. Thread attachment RC 2 M. Dual USB charging adapter 230 V

DATA

ITEM NO.	11138
CABLE LENGTH m	30 m
TOTAL WEIGHT KG	2,90 kg
CASE SIZE MM	B 395 mm L 434 mm H 135 mm
MONITOR	3.5" TFT LCD Monitor 16 M color
CAMERA PROBE	307.200 Pixel (640 x 480)
ILLUMINATION	6 x LED (integrated in camera probe)
PROTECTION CLASS	IP 67 (camera probe and cable)
FIELD OF VIEW	64 °
FOCUSSING DISTANCE	30 mm – 80 mm
POWER SUPPLY	230 V or battery-operated (battery included)
LANGUAGES	DE, EN, FR, ES, PT, IT, NL, DA, SE, NO, FI, PL, CS, HU, RU, IS, LT, SK, SLO, HR, TR
EAN-CODE	9120045476393

ADVANTAGES

- ✓ Protection class IP67
- ✓ Pipe inspection from Ø 14 mm (inside)
- ✓ Ventilation pipes, drainage pipes, sewage pipes and much more
- ✓ Also for cavity inspection and suspended ceilings
- ✓ Lengths 10 m, 30 m or 50 m
- ✓ Memory function/documented evidence
- ✓ Photo (JPG), Video (AVI), Audio
- ✓ Spool with camera cable can be easily unwound or rewound via the X BOARD series

DESCRIPTION

RUNPOCAM RC2 multifunctional camera with cable lengths of 10 m, 30 m and 50 m with coil incl. monitor bracket. In W-Boxx system case - compatible with Sortimo. Extra large 3.5" TFT LCD 16 m colour display, protection class IP67(camera probe and cable), battery operation up to 6 hours. Evidence preservation/storage function: photo, video and audio. CAMERA HEAD with 6 integrated LEDs, enclosed in robust stainless steel head (Ø 13 mm) with RTG Ø 6 mm internal thread. Compatible to all RUNPOTEC products with RTG Ø 6 mm thread (POWER REX, RUNPOSTICKS, RUNPO 1, glass fibre rod Ø 4.5 - 6 - 7.5 - 9 - 11 - 15 mm).

Optimal field of application: For pipe inspections over long distances of up to 50 m. As of 14 mm inner diameter (corresponds to empty pipe Ø 20 mm), but also for larger pipe cross-sections (ventilation systems, drainage systems, sewage pipes etc.). In combination with the RUNPOSTICKS, excellent for cavity wall inspections, suspended ceilings (above high ceiling profiles), manhole and underfloor ducts, maintenance and system inspections.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: RUNPOCAM RC2 with cable incl. reel in system case and incl. accessories: RUNPOGLIDER with front thread, system slide, LED-battery high performance 320 lumen lamp, Micro Memory Card 8 GB, magnetic catch set, connecting thread set RTG Ø 6 mm, catch hook, 2-fold USB charging plug 12 V, flexible attachment 12 cm, USB cable 3 m, 2-fold USB charging plug 230 V, threaded attachment RC 2, USB charging cable for LED-battery lamp

INFORMATION

Combinable plug systems:


RUNPO 1

Length 5 - 30 m



POWER REX

Length 20 m | 30m | 40 m | 50 m




Fibreglass rod Ø 4,5/6/7,5/9/11 mm

Length 30 up to 300 Meter



RUNPOSTICKS

Paket: Comfort | Standard



DATASHEET

POWER REX

Fiberglass rod Ø 3 mm incl. RUNPOGLIDER

Item no.: 10087 | 10088 | 10089 | 10090



VIDEO

RUNPOGLEITER

Click here Video

Click here Productinformation

INCLUDED ACCESSORIES

PATENTED

Achtung! Stromleitend
Attention! electric conductive

INFORMATION

BEGINNING

RUNPOGLIDER with swivel Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread, screwed to strand

ENDING

Endingjoint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA				
ITEM NO.	10087	10088	10089	10090
LENGTH	20 m	30 m	40 m	50 m
TOTAL WEIGHT	1,12 kg	1,24 kg	1,34 kg	1,46 kg
MATERIAL	Fiberglass core with PP Sheath			
TOTAL BREAKING LOAD	120 kg			
BENDING RADIUS	55 mm			
TUBE DIAMETER Ø	for pipe dimension 16 mm - 50 mm			
EAN-CODE	9120045473964	9120045473971	9120045473988	9120045473995

- ADVANTAGES**
- ✓ RUNPOCAM RC 2-compatible
 - ✓ Shear-stable
 - ✓ Also for occupied pipes
 - ✓ Numerous accessories included
 - ✓ Patented RUNPOGLEITER with eyelet and integrated twist compensation
 - ✓ Total breaking load 120 kg

Rec. tube diamter, bending radius and total breaking load of POWER REX Ø 3 mm

Ø				
3 mm	16-50 mm	55 mm	450 Kg	120 Kg

DESCRIPTION

Power Rex - cable pulling device, glass fibre rod Ø 3 mm with end sleeve RUNPOTEC RTG Ø 6 mm thread and the patented RUNPOGLEITER with twist compensation in a practical plastic box The stated total breaking load of 120 kg always refers to the entire product (glass fibre rod including end sleeves). The POWER REX is a slide-in system further developed by RUNPOTEC, which scores with the revolutionary RUNPOGLEITER with twist compensation, a storage compartment for all accessories and high-quality workmanship. Better gliding, higher tensile load, extra large eyelet hole for more cable intake, no need to change the eyelet head. Excellent in combination with the RUNPOTEC RC 2 multifunctional camera.

Optimal field of application: for pipe dimensions 16 mm - 50 mm.

Scope of delivery: POWER REX in plastic box incl. RUNPOGLEITER with twist compensation at the rod tip and end sleeve with RUNPOTEC RTG Ø 6 mm thread at the rod end, 1 x pulling aid, 1 x special adhesive 3g, 1 x cable pulling sleeve 6 - 9 mm with twist compensation, 3 x connecting sleeves Ø 6 mm, 5 x end sleeves Ø 6 mm, 2 x pulling eyes Ø 7 mm

INFORMATION

Compatible with:

RUNPOCAM RC2

Length: 10 m | 30 m | 50 m
Item no. 10139 | 10140 | 10141

Click here Productinformation