

Hallway

COM1 - Concealed wiring
EAN 4007841 086503
Article number 086503



max. 25 x 3 m

2000 W

max. 2000 W



IP20



2 - 2000 lux



5 sec - 60 min



2 - 12 m

iQ

iQ-mode

Teach

Teach mode



connectable via
bluetooth

5 years

manufacturer's
warranty steinel.de/
garantie

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Technical specifications

Dimensions (L x W x H)	67 x 103 x 103 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Bluetooth Mesh
With remote control	No
Version	COM1 - Concealed wiring
PU1, EAN	4007841086503
Type	Presence detector
Application, place	Indoors
Application, room	Indoors, corridor / aisle
Colour	white
Colour, RAL	9003
Includes corner wall mount	No
Installation site	ceiling
Installation	Concealed wiring, Ceiling
IP-rating	IP20
Ambient temperature	from -20 up to 50 °C

Mounting height	2 – 4 m
Mounting height max.	4,00 m
Optimum mounting height	2,8 m
HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	Aisle, 360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	25 x 3 m (75 m ²)
Reach, tangential	25 x 3 m (75 m ²)
Transmitter power	< 1 mW
Functions	Group parameterisation, Semi-/fully automatic, Lighting scenario, Manual

Hallway

COM1 - Concealed wiring
EAN 4007841 086503
Article number 086503



Technical specifications

Technical specifications

Material	Plastic	ON / ON-OFF, Neighbouring group function, Normal / test mode	
Mains power supply	220 – 240 V / 50 – 60 Hz	Twilight setting	2 – 2000 lx
Switching output 1, resistive	2000 W	Time setting	10 s – 60 Min.
Switching output 1, number of LEDs / fluorescent lamps	8 pcs.	Basic light level function	No
Switching output 1, floating	No	Main light adjustable	Yes
Switching output 1, low-voltage halogen lamps	2000 VA	Twilight setting TEACH	Yes
Power consumption	1 W	Constant-lighting control	No
Technology, sensors	High frequency, Light sensor	Interconnection	Yes
		Interconnection via	Bluetooth Mesh
		Product category	Presence detector

Hallway

COM1 - Concealed wiring
EAN 4007841 086503
Article number 086503



Detection Zone



Possible mounting height: 2,00 m - 4,00 m
Orange: radial and tangential

Dimension Drawing



Master circuit diagram

