

SHF 3000

{SHF 2000-7000}

PRODUCT-NO.: 200176

SHF storage heater – high on heat, low on space.

The SHF models are distinguished by their particularly high heating output and low space requirement. With their impressive heat retention capacity, the storage heaters can bridge even long breaks between charging and, in particular, make use of surplus power. With the aid of the integral controller, the room temperature can be controlled precisely using the 7-day timer. If the room is ventilated, the heater switches off automatically.



The main features

Compact, freestanding storage heater with a high heating output

3.0 kW connected load

Integral RT controller with 7-day timer and open window detection

Easily accessible controls with backlit LCD

Long service life

Extremely quiet operation due to low noise crossflow fan

Made in Germany



Type	SHF 2000	SHF 3000	SHF 4000
Part no.	200175	200176	200177
Rated connected load	2 kW	3 kW	4 kW
Height	650 mm	650 mm	650 mm
Depth	275 mm	275 mm	275 mm
Width	605 mm	780 mm	955 mm

Technical data

Power supply	1/N/PE ~ 230V, 3/N/PE ~ 400V	1/N/PE ~ 230V, 3/N/PE ~ 400V	1/N/PE ~ 230V, 3/N/PE ~ 400V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated current	2,9 A	4,3 A	5,8 A
Fuses	10 A	10 A	10 A
Operating noise	30 dB(A)	32 dB(A)	33 dB(A)
Number of stone packs	6	9	12
Weight	32 kg	40 kg	48 kg
Weight (incl. blocks)	118 kg	169 kg	220 kg
Colour	alpine white	alpine white	alpine white



Type	SHF 5000	SHF 6000	SHF 7000
Part no.	200178	200179	200180
Rated connected load	5 kW	6 kW	7 kW
Height	650 mm	650 mm	650 mm
Depth	275 mm	275 mm	275 mm
Width	1130 mm	1305 mm	1480 mm

Technical data

Power supply	1/N/PE ~ 230V, 3/N/PE ~ 400V	1/N/PE ~ 230V, 3/N/PE ~ 400V	1/N/PE ~ 230V, 3/N/PE ~ 400V
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated current	7,2 A	8,7 A	10,1 A
Fuses	16 A	16 A	16 A
Operating noise	34 dB(A)	34 dB(A)	34 dB(A)
Number of stone packs	15	18	21
Weight	56 kg	64 kg	72 kg
Weight (incl. blocks)	271 kg	322 kg	373 kg
Colour	alpine white	alpine white	alpine white

Depth excluding 30 mm wall clearance mesh

Weight including storage blocks

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.