


Aquastar T8

F14W/T8 Aquastar
0002212



Product features

- Colour temperature 10,000K recreating the tropical light spectrum. For fresh and marine aquariums. Excellent combination with DaylightStar. Outstanding results in combination with Daylightstar.



NOTES

undefined

PRODUCT OVERVIEW

| | |
|----------------------------|---|
| IPC Code | 0002212 |
| Product name | F14W/T8 Aquastar |
| Technology | Fluorescent |
| Watt (Rated) (W) | 14.00 |
| Lamp shape | Tubular |
| Type | T8 |
| Cap/Base | G13 |
| Lamp finish | Coated |
| Fixture rating | Open |
| General application | Hospitality,Retail,Residential & Consumer |
| Certifications | 00 |
| ETIM Class | EC000108 |
| Luminous flux (lm) | 525 |
| Colour temperature (K) | 10000 |
| Light colour | Aquastar |
| Wattage (W) | 14.00 |
| Product Voltage (V) | 38 |
| Dimmable | Yes |
| Average life (Nominal) (h) | 10000 |
| Product EAN number | 5410288022123 |

Aquastar T8

F14W/T8 Aquastar
0002212

DATA TABLE

General data

| | |
|----------------------------------|---|
| IPC Code | 0002212 |
| Product name | F14W/T8 Aquastar |
| Technology | Fluorescent |
| Watt (Rated) (W) | 14.00 |
| Lamp shape | Tubular |
| Type | T8 |
| Cap/Base | G13 |
| Lamp finish | Coated |
| Fixture rating | Open |
| General application | Hospitality,Retail,Residential & Consumer |
| Operating temperature range (°C) | -15°C to +50°C |
| Certifications | 00 |
| ETIM Class | EC000108 |

Optical data

| | |
|--|----------|
| Luminous flux (lm) | 525 |
| Ambient temperature for maximum luminous flux (°C) | 25 |
| Colour temperature (K) | 10000 |
| Light colour | Aquastar |
| Adjustable chromaticity | N |

Electrical data

| | |
|-----------------------------------|-------|
| Wattage (W) | 14.00 |
| Watt (Rated) - High frequency (W) | 13.00 |
| Current (A) | 0.395 |
| Product Voltage (V) | 38 |
| Control gear required | Yes |
| Transformer required | No |
| Dimmable | Yes |
| Drive current (mA) | 395 |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 10000 |
| Average life (Rated) (h) | 10000 |

Physical data

| | |
|-------------------------------------|-------------|
| Nominal Product Length (mm) | 360.0 |
| Nominal Product Diameter (mm) | 26 |
| Max. Length base to base (mm) - A | 361.2 |
| Length base to pin Min-Max (mm) - B | 365.8-368.3 |
| Max. Lamp Length (mm) - C/L | 375.4 |
| Max. Lamp Diameter (mm) - D | 28.0 |
| Weight (kg) | 0.054 |

Aquastar T8

F14W/T8 Aquastar
0002212



Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288022123 |
| Packaging single length / height (cm) | 37.6 |
| Packaging single width (cm) | 2.9 |
| Packaging single depth (cm) | 2.8 |
| DUN14 (outer) | 15410288022120 |
| Units per outer package | 25 |
| Packaging outer length / height (cm) | 40.0 |
| Packaging outer width (cm) | 15.5 |
| Packaging outer depth (cm) | 15.0 |

Safety data

| | |
|-------------------------------------|--------------------------------|
| Lamp mercury content (mg) | 2.80 |
| Breakage cleaning instructions | Applicable |
| Special purpose lamp | Yes |
| Intended purpose | Fresh / Marine water aquariums |
| Suitable for household illumination | No |
| Safety message | Not suitable for household |

PHOTOMETRY



TECHNICAL DRAWINGS

